



# Network switch

Products Selecting Type Manual

Shenzhen Hi-Net Technology Co.,Ltd

## S1005



- IEEE802.3, IEEE 802.3u
- 5 10/100Base-TX ports
- 1Gbps switching bandwidth
- 1K MAC address
- Reliable Power Adapter
- Desktop

Network switch

## S1008



- IEEE802.3, IEEE 802.3u
- 8 10/100Base-TX ports
- 1.6Gbps switching bandwidth
- 1K MAC address
- Reliable Power Adapter
- Desktop

Network switch

## S1605



- IEEE802.3, IEEE 802.3u, IEEE 802.3ab, IEEE802.3z
- 5 10/100/1000Base-TX ports
- 10Gbps switching bandwidth
- 2K MAC address
- Reliable Power Adapter
- Desktop

Network switch

## S1608



- IEEE802.3, IEEE 802.3u IEEE 802.3ab, IEEE802.3z
- 8 10/100/1000Base-TX ports
- 16Gbps switching bandwidth
- 8K MAC address
- Reliable Power Adapter

Network switch

## S2016



- IEEE802.3, IEEE 802.3u
- 16 10/100Base-TX ports
- 8K MAC address
- 3.2Gbps switching bandwidth
- 19" rack-mounted metal case
- Built-in power supply

Network switch

## S2018



- IEEE802.3, IEEE 802.3u IEEE 802.3ab, IEEE802.3z
- 16 10/100Base-TX ports
- 2x1000Combo port
- 8K MAC address
- 7.2Gbps switching bandwidth
- Built-in power supply

Network switch

## S2024



- IEEE802.3, IEEE 802.3u
- 24 10/100Base-TX ports
- 8K MAC address
- 4.8Gbps switching bandwidth
- 19" rack-mounted metal case
- Built-in power supply

Network switch

## S2026



- IEEE802.3, IEEE 802.3u IEEE 802.3ab, IEEE802.3z
- 24 10/100Base-TX ports
- 2x1000Combo port
- 4K MAC address
- 8.8Gbps switching bandwidth
- Built-in power supply

Network switch

## S2616



- IEEE802.3, IEEE 802.3u, IEEE 802.3ab, IEEE802.3z
- 16 10/100/1000 Base-TX ports
- 32Gbps switching bandwidth
- 19" rack-mounted metal case
- 8k MAC address
- Built-in power supply

Network switch

## S2624



- IEEE802.3, IEEE 802.3u, IEEE 802.3ab, IEEE802.3z
- 24 10/100/1000 Base-TX ports
- 48Gbps switching bandwidth
- 8k MAC address
- Built-in power supply
- Unmanaged

Network switch

## S2616R



- IEEE802.3, IEEE 802.3u, IEEE 802.3ab, IEEE802.3z
- 16 10/100/1000 Base-TX ports
- 32Gbps switching bandwidth
- 8k MAC address
- Built-in power supply
- Unmanaged

Network switch

## S2618R



- IEEE802.3, IEEE 802.3u, IEEE 802.3ab, IEEE802.3z
- 16 10/100/1000 Base-TX ports
- 2 1000M SFP ports
- 36Gbps switching bandwidth
- 8k MAC address
- Built-in power supply
- Unmanaged

Network switch

## S2624R



- IEEE802.3, IEEE 802.3u, IEEE 802.3ab, IEEE802.3z
- 24 10/100/1000 Base-TX ports
- 48Gbps switching bandwidth
- 8k MAC address
- Built-in power supply
- Unmanaged

Network switch

## S2626R



- IEEE802.3, IEEE 802.3u, IEEE 802.3ab, IEEE802.3z
- 24 10/100/1000 Base-TX ports
- 2 1000M SFP ports
- 52Gbps switching bandwidth
- 8k MAC address
- Built-in power supply
- Unmanaged

Network switch

## S2216



- IEEE802.3, IEEE 802.3u
- 16 10/100Base-TX ports
- 3.2Gbps switching bandwidth
- Port mirror and bandwidth control
- IEEE802.3x Flow control
- Built-in power supply
- Web-smart managed

Network switch

## S2218



- IEEE802.3, IEEE 802.3u, IEEE 802.3ab, IEEE802.3z
- 16 10/100Base-TX ports
- 2x1000Combo port
- 7.2Gbps switching bandwidth
- Port mirror and bandwidth control
- IEEE802.3x Flow control
- Built-in power supply
- Web-smart managed

Network switch

## S2224



- IEEE802.3, IEEE 802.3u
- Provides 24 10/100Base-TX ports
- 4.8Gbps switching bandwidth
- IGMP snooping support version 1,2
- Port mirror and bandwidth control
- IEEE802.3x Flow control
- Built-in power supply
- Web-smart managed

Network switch

## S2226



- IEEE802.3, IEEE 802.3u, IEEE 802.3ab, IEEE802.3z
- 24 10/100Base-TX ports
- 2x1000Combo port
- 8.8Gbps switching bandwidth
- Port mirror and bandwidth control
- IEEE802.3x Flow control
- Built-in power supply
- Web-smart managed

Network switch

### S2318R



- IEEE802.3, IEEE 802.3u  
IEEE 802.3ab, IEEE802.3z
- 16 10/100 Base-TX ports
- 2x1000Combo port
- 8k MAC address
- 7.2Gbps switching bandwidth
- Built-in power supply
- Managed

Network switch

### S2326R



- IEEE802.3, IEEE 802.3u  
IEEE 802.3ab, IEEE802.3z
- 24 10/100 Base-TX ports
- 2x1000Combo port
- 8k MAC address
- 8.8Gbps switching bandwidth
- Built-in power supply
- Managed

Network switch

### S2322R



- IEEE802.3, IEEE 802.3u  
IEEE 802.3ab, IEEE802.3z
- 16 10/100 Base-TX ports
- 2x1000 SFP+2x1000Combo port
- 8k MAC address
- 11.2Gbps switching bandwidth
- Built-in power supply
- Managed

Network switch

### S2330R



- IEEE802.3, IEEE 802.3u  
IEEE 802.3ab, IEEE802.3z
- 24 10/100 Base-TX ports
- 2x1000 SFP+2x1000Combo port
- 8k MAC address
- 12.8Gbps switching bandwidth
- Built-in power supply
- Managed

Network switch

### S2910D



- IEEE802.3, IEEE 802.3u  
IEEE 802.3ab, IEEE802.3z
- 8 10/100/1000Base-TX ports
- 2x1000 SFP Shared
- 20Gbps switching capacity
- 8K MAC address
- Built-in Power Supply
- L2+Full managed
- 13" 1U Rack-mount

Network switch

### S2912



- IEEE802.3, IEEE 802.3u  
IEEE 802.3ab, IEEE802.3z
- 8 10/100/1000Base-TX ports
- 4x1000 SFP
- 24Gbps switching capacity
- 8K MAC address
- Built-in Power Supply
- L2+Full managed
- 13" 1U Rack-mount

Network switch

### S2918



- IEEE802.3, IEEE 802.3u  
IEEE 802.3ab, IEEE802.3z
- 16 10/100/1000Base-TX ports
- 2x1000 SFP
- 8K MAC address
- 32Gbps switching capacity
- Built-in Power Supply
- L2+Full managed

Network switch

### S2928



- IEEE802.3, IEEE 802.3u  
IEEE 802.3ab, IEEE802.3z
- 24 10/100/1000Base-TX ports
- 4x1000 SFP Shared
- 8K MAC address
- 48Gbps switching capacity
- Built-in Power Supply
- L2+Full managed

Network switch

### S2918R



- IEEE802.3, IEEE 802.3u  
IEEE 802.3ab, IEEE802.3z
- 16 10/100/1000Base-TX ports
- 2x1000 SFP
- 8K MAC address
- 36Gbps switching capacity
- Built-in Power Supply
- L2+Full managed

Network switch

## S2922R



- IEEE802.3, IEEE 802.3u  
IEEE 802.3ab, IEEE802.3z
- 16 10/100/1000Base-TX ports
- 2x1000 SFP+2x1000 Combo port
- 40Gbps switching capacity
- 8K MAC address
- Built-in Power Supply
- L2+Full managed

Network switch

## S2926R



- IEEE802.3, IEEE 802.3u  
IEEE 802.3ab, IEEE802.3z
- 24 10/100/1000Base-TX ports
- 2x1000 SFP
- 52Gbps switching capacity
- 8K MAC address
- Built-in Power Supply
- L2+Full managed

Network switch

## S2930R



- IEEE802.3, IEEE 802.3u  
IEEE 802.3ab, IEEE802.3z
- 24 10/100/1000Base-TX ports
- 2x1000 SFP+2x1000Combo port
- 56Gbps switching capacity
- 8K MAC address
- Built-in Power Supply
- L2+Full managed

Network switch

## S3020



- IEEE802.3, IEEE 802.3u  
IEEE 802.3ab, IEEE802.3z
- 16 10/100/1000Base-TX ports
- 4x1000 SFP
- 40Gbps switching capacity
- 16K MAC address
- Built-in Power Supply
- L3 Lite Managed

Network switch

## S3028



- IEEE802.3, IEEE 802.3u  
IEEE 802.3ab, IEEE802.3z
- 24 10/100/1000Base-TX ports
- 4x1000 SFP
- 56Gbps switching capacity
- 16K MAC address
- Built-in Power Supply
- L3 Lite Managed

Network switch

## S5020



- IEEE802.3, IEEE 802.3u  
IEEE 802.3ab, IEEE802.3z
- 16 10/100/1000Base-TX ports
- 4x10Gbps SFP
- 112Gbps switching capacity
- 16K MAC address
- Built-in Power Supply
- L3 Lite Managed

Network switch

## S5028



- IEEE802.3, IEEE 802.3u  
IEEE 802.3ab, IEEE802.3z
- 24 10/100/1000Base-TX ports
- 4x10Gbps SFP
- 128Gbps switching capacity
- 16K MAC address
- Built-in Power Supply
- L3 Lite Managed

Network switch

## MC101-SC



- IEEE 802.3 10Base-T
- IEEE 802.3u 100BaseT(X)
- IEEE 802.3x flow control
- RJ45 twisted pair
- Optical Port: SC, ST or FC
- Single-Mode,Dual fiber, 1310nm
- power input: DC5V
- Transmission Range :20KM

media converters

## MC201-SC



- IEEE 802.3z 1000BaseX
- IEEE 802.3ab 1000BaseT(X)
- IEEE 802.3 10Base-T
- IEEE 802.3u 100BaseT(X)
- IEEE 802.3x flow control
- Optical Port: SC, ST or FC
- Single-Mode,Dual fiber, 1310nm
- power input: DC5V
- Transmission Range :20KM

media converters

### MC121-SC



- IEEE 802.3 10Base-T
- IEEE 802.3u 100Base(X)
- IEEE 802.3x flow control
- Optical Port: SC, ST or FC
- Single-Mode, Single fiber, 1310nm,
- power input: DC5V,
- Transmission Range :20KM

media convertors

### MC221-SC



- IEEE 802.3 10Base-T
- IEEE 802.3u 100Base(X)
- IEEE 802.3z 1000BaseX
- IEEE 802.3ab 1000BaseT(X)
- IEEE 802.3x flow control
- Optical Port: SC, ST or FC
- Single-Mode, Single fiber, 1310nm
- power input: DC5V
- Transmission Range :20KM

media convertors

### MC201-LC



- IEEE 802.3 for 10Base-T
- IEEE 802.3u for 100BaseT(X)
- IEEE 802.3z for 1000BaseX
- IEEE 802.3ab for 1000BaseT(X)
- Power input: DC5V,
- Unmanaged

media convertors

### MC201-SC-P



- IEEE 802.3 af/at
- IEEE 802.3 for 10Base-T
- IEEE 802.3u for 100BaseT(X)
- IEEE 802.3z for 1000BaseX
- IEEE 802.3ab for 1000BaseT(X)
- Optical Port: SC, ST or FC
- Single-Mode Single fiber, 1310nm,
- Power input: AC100V~260V
- Transmission Range :20KM

media convertors

### MC101-SC-P



- IEEE 802.3 af/at
- IEEE 802.3 10Base-T
- IEEE 802.3u 100BaseT(X)
- IEEE 802.3x flow control
- Optical Port: SC, ST or FC (Optional)
- Single-Mode, Dual fiber, 1310nm
- Power input: AC100V~260V
- Transmission Range :20KM

media convertors

### SFP Module



- Wave-length: 1310nm, Rate: 1.25Gbps
- Delivery distance : 20km
- Operating temperature: -40 ~ 80°C
- Relative humidity: 5% ~ 90% (non-condensing)

Switch Accessories

## Contact us

### Shenzhen Hi-Net Technology Co., Ltd

3F, 4 Building, Anda Industrial Zone, Chongqing Rd, Fuyong Town, Baoan District, Shenzhen City, Guangdong Province, PR China

TEL: +86-755-23706700

FAX: +86-755-27330546

E-mail: sales@szhi-net.com

Web-side: www.szhi-net.com